





AS-568




| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-001 | -001 | 0.74 | 0.10 | 1.02 | 0.08 | 0.029 | 0.004 | 0.040 | 0.003 |
| 2-002 | -002 | 1.07 | 0.10 | 1.27 | 0.08 | 0.042 | 0.004 | 0.050 | 0.003 |
| 2-003 | -003 | 1.42 | 0.10 | 1.52 | 0.08 | 0.056 | 0.004 | 0.060 | 0.003 |
| 2-004 | -004 | 1.78 | 0.13 | 1.78 | 0.08 | 0.070 | 0.005 | 0.070 | 0.003 |
| 2-005 | -005 | 2.57 | 0.13 | 1.78 | 0.08 | 0.101 | 0.005 | 0.070 | 0.003 |
| 2-006 | -006 | 2.90 | 0.13 | 1.78 | 0.08 | 0.114 | 0.005 | 0.070 | 0.003 |
| 2-007 | -007 | 3.68 | 0.13 | 1.78 | 0.08 | 0.145 | 0.005 | 0.070 | 0.003 |
| 2-008 | -008 | 4.47 | 0.13 | 1.78 | 0.08 | 0.176 | 0.005 | 0.070 | 0.003 |
| 2-009 | -009 | 5.28 | 0.13 | 1.78 | 0.08 | 0.208 | 0.005 | 0.070 | 0.003 |
| 2-010 | -010 | 6.07 | 0.13 | 1.78 | 0.08 | 0.239 | 0.005 | 0.070 | 0.003 |
| 2-011 | -011 | 7.65 | 0.13 | 1.78 | 0.08 | 0.301 | 0.005 | 0.070 | 0.003 |
| 2-012 | -012 | 9.25 | 0.13 | 1.78 | 0.08 | 0.364 | 0.005 | 0.070 | 0.003 |
| 2-013 | -013 | 10.82 | 0.13 | 1.78 | 0.08 | 0.426 | 0.005 | 0.070 | 0.003 |
| 2-014 | -014 | 12.42 | 0.13 | 1.78 | 0.08 | 0.489 | 0.005 | 0.070 | 0.003 |
| 2-015 | -015 | 14.00 | 0.18 | 1.78 | 0.08 | 0.551 | 0.007 | 0.070 | 0.003 |
| 2-016 | -016 | 15.60 | 0.23 | 1.78 | 0.08 | 0.614 | 0.009 | 0.070 | 0.003 |
| 2-017 | -017 | 17.17 | 0.23 | 1.78 | 0.08 | 0.676 | 0.009 | 0.070 | 0.003 |
| 2-018 | -018 | 18.77 | 0.23 | 1.78 | 0.08 | 0.739 | 0.009 | 0.070 | 0.003 |
| 2-019 | -019 | 20.35 | 0.23 | 1.78 | 0.08 | 0.801 | 0.009 | 0.070 | 0.003 |
| 2-020 | -020 | 21.95 | 0.23 | 1.78 | 0.08 | 0.864 | 0.009 | 0.070 | 0.003 |
| 2-021 | -021 | 23.52 | 0.23 | 1.78 | 0.08 | 0.926 | 0.009 | 0.070 | 0.003 |
| 2-022 | -022 | 25.12 | 0.25 | 1.78 | 0.08 | 0.989 | 0.010 | 0.070 | 0.003 |
| 2-023 | -023 | 26.70 | 0.25 | 1.78 | 0.08 | 1.051 | 0.010 | 0.070 | 0.003 |
| 2-024 | -024 | 28.30 | 0.25 | 1.78 | 0.08 | 1.114 | 0.010 | 0.070 | 0.003 |
| 2-025 | -025 | 29.87 | 0.28 | 1.78 | 0.08 | 1.176 | 0.011 | 0.070 | 0.003 |
| 2-026 | -026 | 31.47 | 0.28 | 1.78 | 0.08 | 1.239 | 0.011 | 0.070 | 0.003 |
| 2-027 | -027 | 33.05 | 0.28 | 1.78 | 0.08 | 1.301 | 0.011 | 0.070 | 0.003 |
| 2-028 | -028 | 34.65 | 0.33 | 1.78 | 0.08 | 1.364 | 0.013 | 0.070 | 0.003 |

AS-568




| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-029 | -029 | 37.82 | 0.33 | 1.78 | 0.08 | 1.489 | 0.013 | 0.070 | 0.003 |
| 2-030 | -030 | 41.00 | 0.33 | 1.78 | 0.08 | 1.614 | 0.013 | 0.070 | 0.003 |
| 2-031 | -031 | 44.17 | 0.38 | 1.78 | 0.08 | 1.739 | 0.015 | 0.070 | 0.003 |
| 2-032 | -032 | 47.35 | 0.38 | 1.78 | 0.08 | 1.864 | 0.015 | 0.070 | 0.003 |
| 2-033 | -033 | 50.52 | 0.46 | 1.78 | 0.08 | 1.989 | 0.018 | 0.070 | 0.003 |
| 2-034 | -034 | 53.70 | 0.46 | 1.78 | 0.08 | 2.114 | 0.018 | 0.070 | 0.003 |
| 2-035 | -035 | 56.87 | 0.46 | 1.78 | 0.08 | 2.239 | 0.018 | 0.070 | 0.003 |
| 2-036 | -036 | 60.05 | 0.46 | 1.78 | 0.08 | 2.364 | 0.018 | 0.070 | 0.003 |
| 2-037 | -037 | 63.22 | 0.46 | 1.78 | 0.08 | 2.489 | 0.018 | 0.070 | 0.003 |
| 2-038 | -038 | 66.40 | 0.51 | 1.78 | 0.08 | 2.614 | 0.020 | 0.070 | 0.003 |
| 2-039 | -039 | 69.57 | 0.51 | 1.78 | 0.08 | 2.739 | 0.020 | 0.070 | 0.003 |
| 2-040 | -040 | 72.75 | 0.51 | 1.78 | 0.08 | 2.864 | 0.020 | 0.070 | 0.003 |
| 2-041 | -041 | 75.92 | 0.61 | 1.78 | 0.08 | 2.989 | 0.024 | 0.070 | 0.003 |
| 2-042 | -042 | 82.27 | 0.61 | 1.78 | 0.08 | 3.239 | 0.024 | 0.070 | 0.003 |
| 2-043 | -043 | 88.62 | 0.61 | 1.78 | 0.08 | 3.489 | 0.024 | 0.070 | 0.003 |
| 2-044 | -044 | 94.97 | 0.69 | 1.78 | 0.08 | 3.739 | 0.027 | 0.070 | 0.003 |
| 2-045 | -045 | 101.32 | 0.69 | 1.78 | 0.08 | 3.989 | 0.027 | 0.070 | 0.003 |
| 2-046 | -046 | 107.67 | 0.76 | 1.78 | 0.08 | 4.239 | 0.030 | 0.070 | 0.003 |
| 2-047 | -047 | 114.02 | 0.76 | 1.78 | 0.08 | 4.489 | 0.030 | 0.070 | 0.003 |
| 2-048 | -048 | 120.37 | 0.76 | 1.78 | 0.08 | 4.739 | 0.030 | 0.070 | 0.003 |
| 2-049 | -049 | 126.72 | 0.94 | 1.78 | 0.08 | 4.989 | 0.037 | 0.070 | 0.003 |
| 2-050 | -050 | 133.07 | 0.94 | 1.78 | 0.08 | 5.239 | 0.037 | 0.070 | 0.003 |
| 2-102 | -102 | 1.24 | 0.13 | 2.62 | 0.08 | 0.049 | 0.005 | 0.103 | 0.003 |
| 2-103 | -103 | 2.06 | 0.13 | 2.62 | 0.08 | 0.081 | 0.005 | 0.103 | 0.003 |
| 2-104 | -104 | 2.84 | 0.13 | 2.62 | 0.08 | 0.112 | 0.005 | 0.103 | 0.003 |
| 2-105 | -105 | 3.63 | 0.13 | 2.62 | 0.08 | 0.143 | 0.005 | 0.103 | 0.003 |
| 2-106 | -106 | 4.42 | 0.13 | 2.62 | 0.08 | 0.174 | 0.005 | 0.103 | 0.003 |
| 2-107 | -107 | 5.23 | 0.13 | 2.62 | 0.08 | 0.206 | 0.005 | 0.103 | 0.003 |

AS-568




| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-108 | -108 | 6.02 | 0.13 | 2.62 | 0.08 | 0.237 | 0.005 | 0.103 | 0.003 |
| 2-109 | -109 | 7.59 | 0.13 | 2.62 | 0.08 | 0.299 | 0.005 | 0.103 | 0.003 |
| 2-110 | -110 | 9.19 | 0.13 | 2.62 | 0.08 | 0.362 | 0.005 | 0.103 | 0.003 |
| 2-111 | -111 | 10.77 | 0.13 | 2.62 | 0.08 | 0.424 | 0.005 | 0.103 | 0.003 |
| 2-112 | -112 | 12.37 | 0.13 | 2.62 | 0.08 | 0.487 | 0.005 | 0.103 | 0.003 |
| 2-113 | -113 | 13.94 | 0.18 | 2.62 | 0.08 | 0.549 | 0.007 | 0.103 | 0.003 |
| 2-114 | -114 | 15.54 | 0.23 | 2.62 | 0.08 | 0.612 | 0.009 | 0.103 | 0.003 |
| 2-115 | -115 | 17.12 | 0.23 | 2.62 | 0.08 | 0.674 | 0.009 | 0.103 | 0.003 |
| 2-116 | -116 | 18.72 | 0.23 | 2.62 | 0.08 | 0.737 | 0.009 | 0.103 | 0.003 |
| 2-117 | -117 | 20.29 | 0.25 | 2.62 | 0.08 | 0.799 | 0.010 | 0.103 | 0.003 |
| 2-118 | -118 | 21.89 | 0.25 | 2.62 | 0.08 | 0.862 | 0.010 | 0.103 | 0.003 |
| 2-119 | -119 | 23.47 | 0.25 | 2.62 | 0.08 | 0.924 | 0.010 | 0.103 | 0.003 |
| 2-120 | -120 | 25.07 | 0.25 | 2.62 | 0.08 | 0.987 | 0.010 | 0.103 | 0.003 |
| 2-121 | -121 | 26.64 | 0.25 | 2.62 | 0.08 | 1.049 | 0.010 | 0.103 | 0.003 |
| 2-122 | -122 | 28.24 | 0.25 | 2.62 | 0.08 | 1.112 | 0.010 | 0.103 | 0.003 |
| 2-123 | -123 | 29.82 | 0.30 | 2.62 | 0.08 | 1.174 | 0.012 | 0.103 | 0.003 |
| 2-124 | -124 | 31.42 | 0.30 | 2.62 | 0.08 | 1.237 | 0.012 | 0.103 | 0.003 |
| 2-125 | -125 | 32.99 | 0.30 | 2.62 | 0.08 | 1.299 | 0.012 | 0.103 | 0.003 |
| 2-126 | -126 | 34.59 | 0.30 | 2.62 | 0.08 | 1.362 | 0.012 | 0.103 | 0.003 |
| 2-127 | -127 | 36.17 | 0.30 | 2.62 | 0.08 | 1.424 | 0.012 | 0.103 | 0.003 |
| 2-128 | -128 | 37.77 | 0.30 | 2.62 | 0.08 | 1.487 | 0.012 | 0.103 | 0.003 |
| 2-129 | -129 | 39.34 | 0.38 | 2.62 | 0.08 | 1.549 | 0.015 | 0.103 | 0.003 |
| 2-130 | -130 | 40.94 | 0.38 | 2.62 | 0.08 | 1.612 | 0.015 | 0.103 | 0.003 |
| 2-131 | -131 | 42.52 | 0.38 | 2.62 | 0.08 | 1.674 | 0.015 | 0.103 | 0.003 |
| 2-132 | -132 | 44.12 | 0.38 | 2.62 | 0.08 | 1.737 | 0.015 | 0.103 | 0.003 |
| 2-133 | -133 | 45.69 | 0.38 | 2.62 | 0.08 | 1.799 | 0.015 | 0.103 | 0.003 |
| 2-134 | -134 | 47.29 | 0.38 | 2.62 | 0.08 | 1.862 | 0.015 | 0.103 | 0.003 |
| 2-135 | -135 | 48.90 | 0.43 | 2.62 | 0.08 | 1.925 | 0.017 | 0.103 | 0.003 |

AS-568




| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-136 | -136 | 50.47 | 0.43 | 2.62 | 0.08 | 1.987 | 0.017 | 0.103 | 0.003 |
| 2-137 | -137 | 52.07 | 0.43 | 2.62 | 0.08 | 2.050 | 0.017 | 0.103 | 0.003 |
| 2-138 | -138 | 53.64 | 0.43 | 2.62 | 0.08 | 2.112 | 0.017 | 0.103 | 0.003 |
| 2-139 | -139 | 55.25 | 0.43 | 2.62 | 0.08 | 2.175 | 0.017 | 0.103 | 0.003 |
| 2-140 | -140 | 56.82 | 0.43 | 2.62 | 0.08 | 2.237 | 0.017 | 0.103 | 0.003 |
| 2-141 | -141 | 58.42 | 0.51 | 2.62 | 0.08 | 2.300 | 0.020 | 0.103 | 0.003 |
| 2-142 | -142 | 59.99 | 0.51 | 2.62 | 0.08 | 2.362 | 0.020 | 0.103 | 0.003 |
| 2-143 | -143 | 61.60 | 0.51 | 2.62 | 0.08 | 2.425 | 0.020 | 0.103 | 0.003 |
| 2-144 | -144 | 63.17 | 0.51 | 2.62 | 0.08 | 2.487 | 0.020 | 0.103 | 0.003 |
| 2-145 | -145 | 64.77 | 0.51 | 2.62 | 0.08 | 2.550 | 0.020 | 0.103 | 0.003 |
| 2-146 | -146 | 66.34 | 0.51 | 2.62 | 0.08 | 2.612 | 0.020 | 0.103 | 0.003 |
| 2-147 | -147 | 67.95 | 0.56 | 2.62 | 0.08 | 2.675 | 0.022 | 0.103 | 0.003 |
| 2-148 | -148 | 69.52 | 0.56 | 2.62 | 0.08 | 2.737 | 0.022 | 0.103 | 0.003 |
| 2-149 | -149 | 71.12 | 0.56 | 2.62 | 0.08 | 2.800 | 0.022 | 0.103 | 0.003 |
| 2-150 | -150 | 72.69 | 0.56 | 2.62 | 0.08 | 2.862 | 0.022 | 0.103 | 0.003 |
| 2-151 | -151 | 75.87 | 0.61 | 2.62 | 0.08 | 2.987 | 0.024 | 0.103 | 0.003 |
| 2-152 | -152 | 82.22 | 0.61 | 2.62 | 0.08 | 3.237 | 0.024 | 0.103 | 0.003 |
| 2-153 | -153 | 88.57 | 0.61 | 2.62 | 0.08 | 3.487 | 0.024 | 0.103 | 0.003 |
| 2-154 | -154 | 94.92 | 0.71 | 2.62 | 0.08 | 3.737 | 0.028 | 0.103 | 0.003 |
| 2-155 | -155 | 101.27 | 0.71 | 2.62 | 0.08 | 3.987 | 0.028 | 0.103 | 0.003 |
| 2-156 | -156 | 107.62 | 0.76 | 2.62 | 0.08 | 4.237 | 0.030 | 0.103 | 0.003 |
| 2-157 | -157 | 113.97 | 0.76 | 2.62 | 0.08 | 4.487 | 0.030 | 0.103 | 0.003 |
| 2-158 | -158 | 120.32 | 0.76 | 2.62 | 0.08 | 4.737 | 0.030 | 0.103 | 0.003 |
| 2-159 | -159 | 126.67 | 0.89 | 2.62 | 0.08 | 4.987 | 0.035 | 0.103 | 0.003 |
| 2-160 | -160 | 133.02 | 0.89 | 2.62 | 0.08 | 5.237 | 0.035 | 0.103 | 0.003 |
| 2-161 | -161 | 139.37 | 0.89 | 2.62 | 0.08 | 5.487 | 0.035 | 0.103 | 0.003 |
| 2-162 | -162 | 145.72 | 0.89 | 2.62 | 0.08 | 5.737 | 0.035 | 0.103 | 0.003 |
| 2-163 | -163 | 152.07 | 0.89 | 2.62 | 0.08 | 5.987 | 0.035 | 0.103 | 0.003 |

AS-568




| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-164 | -164 | 158.42 | 1.02 | 2.62 | 0.08 | 6.237 | 0.040 | 0.103 | 0.003 |
| 2-165 | -165 | 164.77 | 1.02 | 2.62 | 0.08 | 6.487 | 0.040 | 0.103 | 0.003 |
| 2-166 | -166 | 171.12 | 1.02 | 2.62 | 0.08 | 6.737 | 0.040 | 0.103 | 0.003 |
| 2-167 | -167 | 177.47 | 1.02 | 2.62 | 0.08 | 6.987 | 0.040 | 0.103 | 0.003 |
| 2-168 | -168 | 183.82 | 1.14 | 2.62 | 0.08 | 7.237 | 0.045 | 0.103 | 0.003 |
| 2-169 | -169 | 190.17 | 1.14 | 2.62 | 0.08 | 7.487 | 0.045 | 0.103 | 0.003 |
| 2-170 | -170 | 196.52 | 1.14 | 2.62 | 0.08 | 7.737 | 0.045 | 0.103 | 0.003 |
| 2-171 | -171 | 202.87 | 1.14 | 2.62 | 0.08 | 7.987 | 0.045 | 0.103 | 0.003 |
| 2-172 | -172 | 209.22 | 1.27 | 2.62 | 0.08 | 8.237 | 0.050 | 0.103 | 0.003 |
| 2-173 | -173 | 215.57 | 1.27 | 2.62 | 0.08 | 8.487 | 0.050 | 0.103 | 0.003 |
| 2-174 | -174 | 221.92 | 1.27 | 2.62 | 0.08 | 8.737 | 0.050 | 0.103 | 0.003 |
| 2-175 | -175 | 228.27 | 1.27 | 2.62 | 0.08 | 8.987 | 0.050 | 0.103 | 0.003 |
| 2-176 | -176 | 234.62 | 1.40 | 2.62 | 0.08 | 9.237 | 0.055 | 0.103 | 0.003 |
| 2-177 | -177 | 240.97 | 1.40 | 2.62 | 0.08 | 9.487 | 0.055 | 0.103 | 0.003 |
| 2-178 | -178 | 247.32 | 1.40 | 2.62 | 0.08 | 9.737 | 0.055 | 0.103 | 0.003 |
| 2-201 | -201 | 4.34 | 0.13 | 3.53 | 0.10 | 0.171 | 0.005 | 0.139 | 0.004 |
| 2-202 | -202 | 5.94 | 0.13 | 3.53 | 0.10 | 0.234 | 0.005 | 0.139 | 0.004 |
| 2-203 | -203 | 7.52 | 0.13 | 3.53 | 0.10 | 0.296 | 0.005 | 0.139 | 0.004 |
| 2-204 | -204 | 9.12 | 0.13 | 3.53 | 0.10 | 0.359 | 0.005 | 0.139 | 0.004 |
| 2-205 | -205 | 10.69 | 0.13 | 3.53 | 0.10 | 0.421 | 0.005 | 0.139 | 0.004 |
| 2-206 | -206 | 12.29 | 0.13 | 3.53 | 0.10 | 0.484 | 0.005 | 0.139 | 0.004 |
| 2-207 | -207 | 13.87 | 0.18 | 3.53 | 0.10 | 0.546 | 0.007 | 0.139 | 0.004 |
| 2-208 | -208 | 15.47 | 0.23 | 3.53 | 0.10 | 0.609 | 0.009 | 0.139 | 0.004 |
| 2-209 | -209 | 17.04 | 0.23 | 3.53 | 0.10 | 0.671 | 0.009 | 0.139 | 0.004 |
| 2-210 | -210 | 18.64 | 0.25 | 3.53 | 0.10 | 0.734 | 0.010 | 0.139 | 0.004 |
| 2-211 | -211 | 20.22 | 0.25 | 3.53 | 0.10 | 0.796 | 0.010 | 0.139 | 0.004 |
| 2-212 | -212 | 21.82 | 0.25 | 3.53 | 0.10 | 0.859 | 0.010 | 0.139 | 0.004 |
| 2-213 | -213 | 23.39 | 0.25 | 3.53 | 0.10 | 0.921 | 0.010 | 0.139 | 0.004 |

AS-568




| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-214 | -214 | 24.99 | 0.25 | 3.53 | 0.10 | 0.984 | 0.010 | 0.139 | 0.004 |
| 2-215 | -215 | 26.57 | 0.25 | 3.53 | 0.10 | 1.046 | 0.010 | 0.139 | 0.004 |
| 2-216 | -216 | 28.17 | 0.30 | 3.53 | 0.10 | 1.109 | 0.012 | 0.139 | 0.004 |
| 2-217 | -217 | 29.74 | 0.30 | 3.53 | 0.10 | 1.171 | 0.012 | 0.139 | 0.004 |
| 2-218 | -218 | 31.34 | 0.30 | 3.53 | 0.10 | 1.234 | 0.012 | 0.139 | 0.004 |
| 2-219 | -219 | 32.92 | 0.30 | 3.53 | 0.10 | 1.296 | 0.012 | 0.139 | 0.004 |
| 2-220 | -220 | 34.52 | 0.30 | 3.53 | 0.10 | 1.359 | 0.012 | 0.139 | 0.004 |
| 2-221 | -221 | 36.09 | 0.30 | 3.53 | 0.10 | 1.421 | 0.012 | 0.139 | 0.004 |
| 2-222 | -222 | 37.69 | 0.38 | 3.53 | 0.10 | 1.484 | 0.015 | 0.139 | 0.004 |
| 2-223 | -223 | 40.87 | 0.38 | 3.53 | 0.10 | 1.609 | 0.015 | 0.139 | 0.004 |
| 2-224 | -224 | 44.04 | 0.38 | 3.53 | 0.10 | 1.734 | 0.015 | 0.139 | 0.004 |
| 2-225 | -225 | 47.22 | 0.46 | 3.53 | 0.10 | 1.859 | 0.018 | 0.139 | 0.004 |
| 2-226 | -226 | 50.39 | 0.46 | 3.53 | 0.10 | 1.984 | 0.018 | 0.139 | 0.004 |
| 2-227 | -227 | 53.57 | 0.46 | 3.53 | 0.10 | 2.109 | 0.018 | 0.139 | 0.004 |
| 2-228 | -228 | 56.74 | 0.51 | 3.53 | 0.10 | 2.234 | 0.020 | 0.139 | 0.004 |
| 2-229 | -229 | 59.92 | 0.51 | 3.53 | 0.10 | 2.359 | 0.020 | 0.139 | 0.004 |
| 2-230 | -230 | 63.09 | 0.51 | 3.53 | 0.10 | 2.484 | 0.020 | 0.139 | 0.004 |
| 2-231 | -231 | 66.27 | 0.51 | 3.53 | 0.10 | 2.609 | 0.020 | 0.139 | 0.004 |
| 2-232 | -232 | 69.44 | 0.61 | 3.53 | 0.10 | 2.734 | 0.024 | 0.139 | 0.004 |
| 2-233 | -233 | 72.62 | 0.61 | 3.53 | 0.10 | 2.859 | 0.024 | 0.139 | 0.004 |
| 2-234 | -234 | 75.79 | 0.61 | 3.53 | 0.10 | 2.984 | 0.024 | 0.139 | 0.004 |
| 2-235 | -235 | 78.97 | 0.61 | 3.53 | 0.10 | 3.109 | 0.024 | 0.139 | 0.004 |
| 2-236 | -236 | 82.14 | 0.61 | 3.53 | 0.10 | 3.234 | 0.024 | 0.139 | 0.004 |
| 2-237 | -237 | 85.32 | 0.61 | 3.53 | 0.10 | 3.359 | 0.024 | 0.139 | 0.004 |
| 2-238 | -238 | 88.49 | 0.61 | 3.53 | 0.10 | 3.484 | 0.024 | 0.139 | 0.004 |
| 2-239 | -239 | 91.67 | 0.71 | 3.53 | 0.10 | 3.609 | 0.028 | 0.139 | 0.004 |
| 2-240 | -240 | 94.84 | 0.71 | 3.53 | 0.10 | 3.734 | 0.028 | 0.139 | 0.004 |
| 2-241 | -241 | 98.02 | 0.71 | 3.53 | 0.10 | 3.859 | 0.028 | 0.139 | 0.004 |

AS-568



| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-242 | -242 | 101.19 | 0.71 | 3.53 | 0.10 | 3.984 | 0.028 | 0.139 | 0.004 |
| 2-243 | -243 | 104.37 | 0.71 | 3.53 | 0.10 | 4.109 | 0.028 | 0.139 | 0.004 |
| 2-244 | -244 | 107.54 | 0.76 | 3.53 | 0.10 | 4.234 | 0.030 | 0.139 | 0.004 |
| 2-245 | -245 | 110.72 | 0.76 | 3.53 | 0.10 | 4.359 | 0.030 | 0.139 | 0.004 |
| 2-246 | -246 | 113.89 | 0.76 | 3.53 | 0.10 | 4.484 | 0.030 | 0.139 | 0.004 |
| 2-247 | -247 | 117.07 | 0.76 | 3.53 | 0.10 | 4.609 | 0.030 | 0.139 | 0.004 |
| 2-248 | -248 | 120.24 | 0.76 | 3.53 | 0.10 | 4.734 | 0.030 | 0.139 | 0.004 |
| 2-249 | -249 | 123.42 | 0.89 | 3.53 | 0.10 | 4.859 | 0.035 | 0.139 | 0.004 |
| 2-250 | -250 | 126.59 | 0.89 | 3.53 | 0.10 | 4.984 | 0.035 | 0.139 | 0.004 |
| 2-251 | -251 | 129.77 | 0.89 | 3.53 | 0.10 | 5.109 | 0.035 | 0.139 | 0.004 |
| 2-252 | -252 | 132.94 | 0.89 | 3.53 | 0.10 | 5.234 | 0.035 | 0.139 | 0.004 |
| 2-253 | -253 | 136.12 | 0.89 | 3.53 | 0.10 | 5.359 | 0.035 | 0.139 | 0.004 |
| 2-254 | -254 | 139.29 | 0.89 | 3.53 | 0.10 | 5.484 | 0.035 | 0.139 | 0.004 |
| 2-255 | -255 | 142.47 | 0.89 | 3.53 | 0.10 | 5.609 | 0.035 | 0.139 | 0.004 |
| 2-256 | -256 | 145.64 | 0.89 | 3.53 | 0.10 | 5.734 | 0.035 | 0.139 | 0.004 |
| 2-257 | -257 | 148.82 | 0.89 | 3.53 | 0.10 | 5.859 | 0.035 | 0.139 | 0.004 |
| 2-258 | -258 | 151.99 | 0.89 | 3.53 | 0.10 | 5.984 | 0.035 | 0.139 | 0.004 |
| 2-259 | -259 | 158.34 | 1.02 | 3.53 | 0.10 | 6.234 | 0.040 | 0.139 | 0.004 |
| 2-260 | -260 | 164.69 | 1.02 | 3.53 | 0.10 | 6.484 | 0.040 | 0.139 | 0.004 |
| 2-261 | -261 | 171.04 | 1.02 | 3.53 | 0.10 | 6.734 | 0.040 | 0.139 | 0.004 |
| 2-262 | -262 | 177.39 | 1.02 | 3.53 | 0.10 | 6.984 | 0.040 | 0.139 | 0.004 |
| 2-263 | -263 | 183.74 | 1.14 | 3.53 | 0.10 | 7.234 | 0.045 | 0.139 | 0.004 |
| 2-264 | -264 | 190.09 | 1.14 | 3.53 | 0.10 | 7.484 | 0.045 | 0.139 | 0.004 |
| 2-265 | -265 | 196.44 | 1.14 | 3.53 | 0.10 | 7.734 | 0.045 | 0.139 | 0.004 |
| 2-266 | -266 | 202.79 | 1.14 | 3.53 | 0.10 | 7.984 | 0.045 | 0.139 | 0.004 |
| 2-267 | -267 | 209.14 | 1.27 | 3.53 | 0.10 | 8.234 | 0.050 | 0.139 | 0.004 |
| 2-268 | -268 | 215.49 | 1.27 | 3.53 | 0.10 | 8.484 | 0.050 | 0.139 | 0.004 |
| 2-269 | -269 | 221.84 | 1.27 | 3.53 | 0.10 | 8.734 | 0.050 | 0.139 | 0.004 |


AS-568



| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-270 | -270 | 228.19 | 1.27 | 3.53 | 0.10 | 8.984 | 0.050 | 0.139 | 0.004 |
| 2-271 | -271 | 234.54 | 1.40 | 3.53 | 0.10 | 9.234 | 0.055 | 0.139 | 0.004 |
| 2-272 | -272 | 240.89 | 1.40 | 3.53 | 0.10 | 9.484 | 0.055 | 0.139 | 0.004 |
| 2-273 | -273 | 247.24 | 1.40 | 3.53 | 0.10 | 9.734 | 0.055 | 0.139 | 0.004 |
| 2-274 | -274 | 253.59 | 1.40 | 3.53 | 0.10 | 9.984 | 0.055 | 0.139 | 0.004 |
| 2-275 | -275 | 266.29 | 1.40 | 3.53 | 0.10 | 10.484 | 0.055 | 0.139 | 0.004 |
| 2-276 | -276 | 278.99 | 1.65 | 3.53 | 0.10 | 10.984 | 0.065 | 0.139 | 0.004 |
| 2-277 | -277 | 291.69 | 1.65 | 3.53 | 0.10 | 11.484 | 0.065 | 0.139 | 0.004 |
| 2-278 | -278 | 304.39 | 1.65 | 3.53 | 0.10 | 11.984 | 0.065 | 0.139 | 0.004 |
| 2-279 | -279 | 329.79 | 1.65 | 3.53 | 0.10 | 12.984 | 0.065 | 0.139 | 0.004 |
| 2-280 | -280 | 355.19 | 1.65 | 3.53 | 0.10 | 13.984 | 0.065 | 0.139 | 0.004 |
| 2-281 | -281 | 380.59 | 1.65 | 3.53 | 0.10 | 14.984 | 0.065 | 0.139 | 0.004 |
| 2-282 | -282 | 405.26 | 1.91 | 3.53 | 0.10 | 15.955 | 0.075 | 0.139 | 0.004 |
| 2-283 | -283 | 430.66 | 2.03 | 3.53 | 0.10 | 16.955 | 0.080 | 0.139 | 0.004 |
| 2-284 | -284 | 456.06 | 2.16 | 3.53 | 0.10 | 17.955 | 0.085 | 0.139 | 0.004 |
| 2-309 | -309 | 10.46 | 0.13 | 5.33 | 0.13 | 0.412 | 0.005 | 0.210 | 0.005 |
| 2-310 | -310 | 12.07 | 0.13 | 5.33 | 0.13 | 0.475 | 0.005 | 0.210 | 0.005 |
| 2-311 | -311 | 13.64 | 0.18 | 5.33 | 0.13 | 0.537 | 0.007 | 0.210 | 0.005 |
| 2-312 | -312 | 15.24 | 0.23 | 5.33 | 0.13 | 0.600 | 0.009 | 0.210 | 0.005 |
| 2-313 | -313 | 16.81 | 0.23 | 5.33 | 0.13 | 0.662 | 0.009 | 0.210 | 0.005 |
| 2-314 | -314 | 18.42 | 0.25 | 5.33 | 0.13 | 0.725 | 0.010 | 0.210 | 0.005 |
| 2-315 | -315 | 19.99 | 0.25 | 5.33 | 0.13 | 0.787 | 0.010 | 0.210 | 0.005 |
| 2-316 | -316 | 21.59 | 0.25 | 5.33 | 0.13 | 0.850 | 0.010 | 0.210 | 0.005 |
| 2-317 | -317 | 23.16 | 0.25 | 5.33 | 0.13 | 0.912 | 0.010 | 0.210 | 0.005 |
| 2-318 | -318 | 24.77 | 0.25 | 5.33 | 0.13 | 0.975 | 0.010 | 0.210 | 0.005 |
| 2-319 | -319 | 26.34 | 0.25 | 5.33 | 0.13 | 1.037 | 0.010 | 0.210 | 0.005 |
| 2-320 | -320 | 27.94 | 0.30 | 5.33 | 0.13 | 1.100 | 0.012 | 0.210 | 0.005 |
| 2-321 | -321 | 29.51 | 0.30 | 5.33 | 0.13 | 1.162 | 0.012 | 0.210 | 0.005 |




AS-568



| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-322 | -322 | 31.12 | 0.30 | 5.33 | 0.13 | 1.225 | 0.012 | 0.210 | 0.005 |
| 2-323 | -323 | 32.69 | 0.30 | 5.33 | 0.13 | 1.287 | 0.012 | 0.210 | 0.005 |
| 2-324 | -324 | 34.29 | 0.30 | 5.33 | 0.13 | 1.350 | 0.012 | 0.210 | 0.005 |
| 2-325 | -325 | 37.47 | 0.38 | 5.33 | 0.13 | 1.475 | 0.015 | 0.210 | 0.005 |
| 2-326 | -326 | 40.64 | 0.38 | 5.33 | 0.13 | 1.600 | 0.015 | 0.210 | 0.005 |
| 2-327 | -327 | 43.82 | 0.38 | 5.33 | 0.13 | 1.725 | 0.015 | 0.210 | 0.005 |
| 2-328 | -328 | 46.99 | 0.38 | 5.33 | 0.13 | 1.850 | 0.015 | 0.210 | 0.005 |
| 2-329 | -329 | 50.17 | 0.46 | 5.33 | 0.13 | 1.975 | 0.018 | 0.210 | 0.005 |
| 2-330 | -330 | 53.34 | 0.46 | 5.33 | 0.13 | 2.100 | 0.018 | 0.210 | 0.005 |
| 2-331 | -331 | 56.52 | 0.46 | 5.33 | 0.13 | 2.225 | 0.018 | 0.210 | 0.005 |
| 2-332 | -332 | 59.69 | 0.46 | 5.33 | 0.13 | 2.350 | 0.018 | 0.210 | 0.005 |
| 2-333 | -333 | 62.87 | 0.51 | 5.33 | 0.13 | 2.475 | 0.020 | 0.210 | 0.005 |
| 2-334 | -334 | 66.04 | 0.51 | 5.33 | 0.13 | 2.600 | 0.020 | 0.210 | 0.005 |
| 2-335 | -335 | 69.22 | 0.51 | 5.33 | 0.13 | 2.725 | 0.020 | 0.210 | 0.005 |
| 2-336 | -336 | 72.39 | 0.51 | 5.33 | 0.13 | 2.850 | 0.020 | 0.210 | 0.005 |
| 2-337 | -337 | 75.57 | 0.61 | 5.33 | 0.13 | 2.975 | 0.024 | 0.210 | 0.005 |
| 2-338 | -338 | 78.74 | 0.61 | 5.33 | 0.13 | 3.100 | 0.024 | 0.210 | 0.005 |
| 2-339 | -339 | 81.92 | 0.61 | 5.33 | 0.13 | 3.225 | 0.024 | 0.210 | 0.005 |
| 2-340 | -340 | 85.09 | 0.61 | 5.33 | 0.13 | 3.350 | 0.024 | 0.210 | 0.005 |
| 2-341 | -341 | 88.27 | 0.61 | 5.33 | 0.13 | 3.475 | 0.024 | 0.210 | 0.005 |
| 2-342 | -342 | 91.44 | 0.71 | 5.33 | 0.13 | 3.600 | 0.028 | 0.210 | 0.005 |
| 2-343 | -343 | 94.62 | 0.71 | 5.33 | 0.13 | 3.725 | 0.028 | 0.210 | 0.005 |
| 2-344 | -344 | 97.79 | 0.71 | 5.33 | 0.13 | 3.850 | 0.028 | 0.210 | 0.005 |
| 2-345 | -345 | 100.97 | 0.71 | 5.33 | 0.13 | 3.975 | 0.028 | 0.210 | 0.005 |
| 2-346 | -346 | 104.14 | 0.71 | 5.33 | 0.13 | 4.100 | 0.028 | 0.210 | 0.005 |
| 2-347 | -347 | 107.32 | 0.76 | 5.33 | 0.13 | 4.225 | 0.030 | 0.210 | 0.005 |
| 2-348 | -348 | 110.49 | 0.76 | 5.33 | 0.13 | 4.350 | 0.030 | 0.210 | 0.005 |
| 2-349 | -349 | 113.67 | 0.76 | 5.33 | 0.13 | 4.475 | 0.030 | 0.210 | 0.005 |




AS-568



| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-350 | -350 | 116.84 | 0.76 | 5.33 | 0.13 | 4.600 | 0.030 | 0.210 | 0.005 |
| 2-351 | -351 | 120.02 | 0.76 | 5.33 | 0.13 | 4.725 | 0.030 | 0.210 | 0.005 |
| 2-352 | -352 | 123.19 | 0.76 | 5.33 | 0.13 | 4.850 | 0.030 | 0.210 | 0.005 |
| 2-353 | -353 | 126.37 | 0.94 | 5.33 | 0.13 | 4.975 | 0.037 | 0.210 | 0.005 |
| 2-354 | -354 | 129.54 | 0.94 | 5.33 | 0.13 | 5.100 | 0.037 | 0.210 | 0.005 |
| 2-355 | -355 | 132.72 | 0.94 | 5.33 | 0.13 | 5.225 | 0.037 | 0.210 | 0.005 |
| 2-356 | -356 | 135.89 | 0.94 | 5.33 | 0.13 | 5.350 | 0.037 | 0.210 | 0.005 |
| 2-357 | -357 | 139.07 | 0.94 | 5.33 | 0.13 | 5.475 | 0.037 | 0.210 | 0.005 |
| 2-358 | -358 | 142.24 | 0.94 | 5.33 | 0.13 | 5.600 | 0.037 | 0.210 | 0.005 |
| 2-359 | -359 | 145.42 | 0.94 | 5.33 | 0.13 | 5.725 | 0.037 | 0.210 | 0.005 |
| 2-360 | -360 | 148.59 | 0.94 | 5.33 | 0.13 | 5.850 | 0.037 | 0.210 | 0.005 |
| 2-361 | -361 | 151.77 | 0.94 | 5.33 | 0.13 | 5.975 | 0.037 | 0.210 | 0.005 |
| 2-362 | -362 | 158.12 | 1.02 | 5.33 | 0.13 | 6.225 | 0.040 | 0.210 | 0.005 |
| 2-363 | -363 | 164.47 | 1.02 | 5.33 | 0.13 | 6.475 | 0.040 | 0.210 | 0.005 |
| 2-364 | -364 | 170.82 | 1.02 | 5.33 | 0.13 | 6.725 | 0.040 | 0.210 | 0.005 |
| 2-365 | -365 | 177.17 | 1.02 | 5.33 | 0.13 | 6.975 | 0.040 | 0.210 | 0.005 |
| 2-366 | -366 | 183.52 | 1.14 | 5.33 | 0.13 | 7.225 | 0.045 | 0.210 | 0.005 |
| 2-367 | -367 | 189.87 | 1.14 | 5.33 | 0.13 | 7.475 | 0.045 | 0.210 | 0.005 |
| 2-368 | -368 | 196.22 | 1.14 | 5.33 | 0.13 | 7.725 | 0.045 | 0.210 | 0.005 |
| 2-369 | -369 | 202.57 | 1.14 | 5.33 | 0.13 | 7.975 | 0.045 | 0.210 | 0.005 |
| 2-370 | -370 | 208.92 | 1.27 | 5.33 | 0.13 | 8.225 | 0.050 | 0.210 | 0.005 |
| 2-371 | -371 | 215.27 | 1.27 | 5.33 | 0.13 | 8.475 | 0.050 | 0.210 | 0.005 |
| 2-372 | -372 | 221.62 | 1.27 | 5.33 | 0.13 | 8.725 | 0.050 | 0.210 | 0.005 |
| 2-373 | -373 | 227.97 | 1.27 | 5.33 | 0.13 | 8.975 | 0.050 | 0.210 | 0.005 |
| 2-374 | -374 | 234.32 | 1.40 | 5.33 | 0.13 | 9.225 | 0.055 | 0.210 | 0.005 |
| 2-375 | -375 | 240.67 | 1.40 | 5.33 | 0.13 | 9.475 | 0.055 | 0.210 | 0.005 |
| 2-376 | -376 | 247.02 | 1.40 | 5.33 | 0.13 | 9.725 | 0.055 | 0.210 | 0.005 |
| 2-377 | -377 | 253.37 | 1.40 | 5.33 | 0.13 | 9.975 | 0.055 | 0.210 | 0.005 |


AS-568



| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-378 | -378 | 266.07 | 1.52 | 5.33 | 0.13 | 10.475 | 0.060 | 0.210 | 0.005 |
| 2-379 | -379 | 278.77 | 1.52 | 5.33 | 0.13 | 10.975 | 0.060 | 0.210 | 0.005 |
| 2-380 | -380 | 291.47 | 1.65 | 5.33 | 0.13 | 11.475 | 0.065 | 0.210 | 0.005 |
| 2-381 | -381 | 304.17 | 1.65 | 5.33 | 0.13 | 11.975 | 0.065 | 0.210 | 0.005 |
| 2-382 | -382 | 329.57 | 1.65 | 5.33 | 0.13 | 12.975 | 0.065 | 0.210 | 0.005 |
| 2-383 | -383 | 354.97 | 1.78 | 5.33 | 0.13 | 13.975 | 0.070 | 0.210 | 0.005 |
| 2-384 | -384 | 380.37 | 1.78 | 5.33 | 0.13 | 14.975 | 0.070 | 0.210 | 0.005 |
| 2-385 | -385 | 405.26 | 1.91 | 5.33 | 0.13 | 15.955 | 0.075 | 0.210 | 0.005 |
| 2-386 | -386 | 430.66 | 2.03 | 5.33 | 0.13 | 16.955 | 0.080 | 0.210 | 0.005 |
| 2-387 | -387 | 456.06 | 2.16 | 5.33 | 0.13 | 17.955 | 0.085 | 0.210 | 0.005 |
| 2-388 | -388 | 481.46 | 2.29 | 5.33 | 0.13 | 18.955 | 0.090 | 0.210 | 0.005 |
| 2-389 | -389 | 506.86 | 2.41 | 5.33 | 0.13 | 19.955 | 0.095 | 0.210 | 0.005 |
| 2-390 | -390 | 532.26 | 2.41 | 5.33 | 0.13 | 20.955 | 0.095 | 0.210 | 0.005 |
| 2-391 | -391 | 557.66 | 2.54 | 5.33 | 0.13 | 21.955 | 0.100 | 0.210 | 0.005 |
| 2-392 | -392 | 582.68 | 2.67 | 5.33 | 0.13 | 22.940 | 0.105 | 0.210 | 0.005 |
| 2-393 | -393 | 608.08 | 2.79 | 5.33 | 0.13 | 23.940 | 0.110 | 0.210 | 0.005 |
| 2-394 | -394 | 633.48 | 2.92 | 5.33 | 0.13 | 24.940 | 0.115 | 0.210 | 0.005 |
| 2-395 | -395 | 658.88 | 3.05 | 5.33 | 0.13 | 25.940 | 0.120 | 0.210 | 0.005 |
| 2-400 | -400 | 34.29 | 0.33 | 6.99 | 0.15 | 1.350 | 0.013 | 0.275 | 0.006 |
| 2-401 | -401 | 37.47 | 0.36 | 6.99 | 0.15 | 1.475 | 0.014 | 0.275 | 0.006 |
| 2-402 | -402 | 40.64 | 0.39 | 6.99 | 0.15 | 1.600 | 0.015 | 0.275 | 0.006 |
| 2-403 | -403 | 43.82 | 0.41 | 6.99 | 0.15 | 1.725 | 0.016 | 0.275 | 0.006 |
| 2-404 | -404 | 46.99 | 0.44 | 6.99 | 0.15 | 1.850 | 0.017 | 0.275 | 0.006 |
| 2-405 | -405 | 50.17 | 0.46 | 6.99 | 0.15 | 1.975 | 0.018 | 0.275 | 0.006 |
| 2-406 | -406 | 53.34 | 0.48 | 6.99 | 0.15 | 2.100 | 0.019 | 0.275 | 0.006 |
| 2-407 | -407 | 56.52 | 0.51 | 6.99 | 0.15 | 2.225 | 0.020 | 0.275 | 0.006 |
| 2-408 | -408 | 59.69 | 0.54 | 6.99 | 0.15 | 2.350 | 0.021 | 0.275 | 0.006 |
| 2-409 | -409 | 62.87 | 0.56 | 6.99 | 0.15 | 2.475 | 0.022 | 0.275 | 0.006 |




AS-568




| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-410 | -410 | 66.04 | 0.59 | 6.99 | 0.15 | 2.600 | 0.023 | 0.275 | 0.006 |
| 2-411 | -411 | 69.22 | 0.61 | 6.99 | 0.15 | 2.725 | 0.024 | 0.275 | 0.006 |
| 2-412 | -412 | 72.39 | 0.64 | 6.99 | 0.15 | 2.850 | 0.025 | 0.275 | 0.006 |
| 2-413 | -413 | 75.57 | 0.66 | 6.99 | 0.15 | 2.975 | 0.026 | 0.275 | 0.006 |
| 2-414 | -414 | 78.74 | 0.67 | 6.99 | 0.15 | 3.100 | 0.026 | 0.275 | 0.006 |
| 2-415 | -415 | 81.92 | 0.71 | 6.99 | 0.15 | 3.225 | 0.028 | 0.275 | 0.006 |
| 2-416 | -416 | 85.09 | 0.73 | 6.99 | 0.15 | 3.350 | 0.029 | 0.275 | 0.006 |
| 2-417 | -417 | 88.27 | 0.75 | 6.99 | 0.15 | 3.475 | 0.030 | 0.275 | 0.006 |
| 2-418 | -418 | 91.44 | 0.79 | 6.99 | 0.15 | 3.600 | 0.031 | 0.275 | 0.006 |
| 2-419 | -419 | 94.62 | 0.81 | 6.99 | 0.15 | 3.725 | 0.032 | 0.275 | 0.006 |
| 2-420 | -420 | 97.79 | 0.83 | 6.99 | 0.15 | 3.850 | 0.033 | 0.275 | 0.006 |
| 2-421 | -421 | 100.97 | 0.84 | 6.99 | 0.15 | 3.975 | 0.033 | 0.275 | 0.006 |
| 2-422 | -422 | 104.14 | 0.87 | 6.99 | 0.15 | 4.100 | 0.034 | 0.275 | 0.006 |
| 2-423 | -423 | 107.32 | 0.89 | 6.99 | 0.15 | 4.225 | 0.035 | 0.275 | 0.006 |
| 2-424 | -424 | 110.49 | 0.91 | 6.99 | 0.15 | 4.350 | 0.036 | 0.275 | 0.006 |
| 2-425 | -425 | 113.67 | 0.84 | 6.99 | 0.15 | 4.475 | 0.033 | 0.275 | 0.006 |
| 2-426 | -426 | 116.84 | 0.84 | 6.99 | 0.15 | 4.600 | 0.033 | 0.275 | 0.006 |
| 2-427 | -427 | 120.02 | 0.84 | 6.99 | 0.15 | 4.73 | 0.03 | 0.28 | 0.006 |
| 2-428 | -428 | 123.19 | 0.84 | 6.99 | 0.15 | 4.85 | 0.03 | 0.28 | 0.006 |
| 2-429 | -429 | 126.37 | 0.94 | 6.99 | 0.15 | 4.975 | 0.037 | 0.275 | 0.006 |
| 2-430 | -430 | 129.54 | 0.94 | 6.99 | 0.15 | 5.100 | 0.037 | 0.275 | 0.006 |
| 2-431 | -431 | 132.72 | 0.94 | 6.99 | 0.15 | 5.225 | 0.037 | 0.275 | 0.006 |
| 2-432 | -432 | 135.89 | 0.94 | 6.99 | 0.15 | 5.350 | 0.037 | 0.275 | 0.006 |
| 2-433 | -433 | 139.07 | 0.94 | 6.99 | 0.15 | 5.475 | 0.037 | 0.275 | 0.006 |
| 2-434 | -434 | 142.24 | 0.94 | 6.99 | 0.15 | 5.600 | 0.037 | 0.275 | 0.006 |
| 2-435 | -435 | 145.42 | 0.94 | 6.99 | 0.15 | 5.725 | 0.037 | 0.275 | 0.006 |
| 2-436 | -436 | 148.59 | 0.94 | 6.99 | 0.15 | 5.850 | 0.037 | 0.275 | 0.006 |
| 2-437 | -437 | 151.77 | 0.94 | 6.99 | 0.15 | 5.975 | 0.037 | 0.275 | 0.006 |

AS-568



| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-438 | -438 | 158.12 | 1.02 | 6.99 | 0.15 | 6.225 | 0.040 | 0.275 | 0.006 |
| 2-439 | -439 | 164.47 | 1.02 | 6.99 | 0.15 | 6.475 | 0.040 | 0.275 | 0.006 |
| 2-440 | -440 | 170.82 | 1.02 | 6.99 | 0.15 | 6.725 | 0.040 | 0.275 | 0.006 |
| 2-441 | -441 | 177.17 | 1.02 | 6.99 | 0.15 | 6.975 | 0.040 | 0.275 | 0.006 |
| 2-442 | -442 | 183.52 | 1.14 | 6.99 | 0.15 | 7.225 | 0.045 | 0.275 | 0.006 |
| 2-443 | -443 | 189.87 | 1.14 | 6.99 | 0.15 | 7.475 | 0.045 | 0.275 | 0.006 |
| 2-444 | -444 | 196.22 | 1.14 | 6.99 | 0.15 | 7.725 | 0.045 | 0.275 | 0.006 |
| 2-445 | -445 | 202.57 | 1.14 | 6.99 | 0.15 | 7.975 | 0.045 | 0.275 | 0.006 |
| 2-446 | -446 | 215.27 | 1.4 | 6.99 | 0.15 | 8.475 | 0.055 | 0.275 | 0.006 |
| 2-447 | -447 | 227.97 | 1.4 | 6.99 | 0.15 | 8.975 | 0.055 | 0.275 | 0.006 |
| 2-448 | -448 | 240.67 | 1.4 | 6.99 | 0.15 | 9.475 | 0.055 | 0.275 | 0.006 |
| 2-449 | -449 | 253.37 | 1.4 | 6.99 | 0.15 | 9.975 | 0.055 | 0.275 | 0.006 |
| 2-450 | -450 | 266.07 | 1.52 | 6.99 | 0.15 | 10.475 | 0.060 | 0.275 | 0.006 |
| 2-451 | -451 | 278.77 | 1.52 | 6.99 | 0.15 | 10.975 | 0.060 | 0.275 | 0.006 |
| 2-452 | -452 | 291.47 | 1.52 | 6.99 | 0.15 | 11.475 | 0.060 | 0.275 | 0.006 |
| 2-453 | -453 | 304.17 | 1.52 | 6.99 | 0.15 | 11.975 | 0.060 | 0.275 | 0.006 |
| 2-454 | -454 | 316.87 | 1.52 | 6.99 | 0.15 | 12.475 | 0.060 | 0.275 | 0.006 |
| 2-455 | -455 | 329.57 | 1.52 | 6.99 | 0.15 | 12.975 | 0.060 | 0.275 | 0.006 |
| 2-456 | -456 | 342.27 | 1.78 | 6.99 | 0.15 | 13.475 | 0.070 | 0.275 | 0.006 |
| 2-457 | -457 | 354.97 | 1.78 | 6.99 | 0.15 | 13.975 | 0.070 | 0.275 | 0.006 |
| 2-458 | -458 | 367.67 | 1.78 | 6.99 | 0.15 | 14.475 | 0.070 | 0.275 | 0.006 |
| 2-459 | -459 | 380.37 | 1.78 | 6.99 | 0.15 | 14.975 | 0.070 | 0.275 | 0.006 |
| 2-460 | -460 | 393.07 | 1.78 | 6.99 | 0.15 | 15.475 | 0.070 | 0.275 | 0.006 |
| 2-461 | -461 | 405.26 | 1.91 | 6.99 | 0.15 | 15.955 | 0.075 | 0.275 | 0.006 |
| 2-462 | -462 | 417.96 | 1.91 | 6.99 | 0.15 | 16.455 | 0.075 | 0.275 | 0.006 |
| 2-463 | -463 | 430.66 | 2.03 | 6.99 | 0.15 | 16.955 | 0.080 | 0.275 | 0.006 |
| 2-464 | -464 | 443.36 | 2.16 | 6.99 | 0.15 | 17.455 | 0.085 | 0.275 | 0.006 |
| 2-465 | -465 | 456.06 | 2.16 | 6.99 | 0.15 | 17.955 | 0.085 | 0.275 | 0.006 |


AS-568



| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 2-466 | -466 | 468.76 | 2.16 | 6.99 | 0.15 | 18.455 | 0.085 | 0.275 | 0.006 |
| 2-467 | -467 | 481.46 | 2.29 | 6.99 | 0.15 | 18.955 | 0.090 | 0.275 | 0.006 |
| 2-468 | -468 | 494.16 | 2.29 | 6.99 | 0.15 | 19.455 | 0.090 | 0.275 | 0.006 |
| 2-469 | -469 | 506.86 | 2.41 | 6.99 | 0.15 | 19.955 | 0.095 | 0.275 | 0.006 |
| 2-470 | -470 | 532.26 | 2.41 | 6.99 | 0.15 | 20.955 | 0.095 | 0.275 | 0.006 |
| 2-471 | -471 | 557.66 | 2.54 | 6.99 | 0.15 | 21.955 | 0.100 | 0.275 | 0.006 |
| 2-472 | -472 | 582.68 | 2.67 | 6.99 | 0.15 | 22.940 | 0.105 | 0.275 | 0.006 |
| 2-473 | -473 | 608.08 | 2.79 | 6.99 | 0.15 | 23.940 | 0.110 | 0.275 | 0.006 |
| 2-474 | -474 | 633.48 | 2.92 | 6.99 | 0.15 | 24.940 | 0.115 | 0.275 | 0.006 |
| 2-475 | -475 | 658.88 | 3.05 | 6.99 | 0.15 | 25.940 | 0.120 | 0.275 | 0.006 |
| 3-901 | -901 | 4.70 | 0.13 | 1.42 | 0.08 | 0.185 | 0.005 | 0.056 | 0.003 |
| 3-902 | -902 | 6.07 | 0.13 | 1.63 | 0.08 | 0.239 | 0.005 | 0.064 | 0.003 |
| 3-903 | -903 | 7.65 | 0.13 | 1.63 | 0.08 | 0.301 | 0.005 | 0.064 | 0.003 |
| 3-904 | -904 | 8.92 | 0.13 | 1.83 | 0.08 | 0.351 | 0.005 | 0.072 | 0.003 |
| 3-905 | -905 | 10.52 | 0.13 | 1.83 | 0.08 | 0.414 | 0.005 | 0.072 | 0.003 |
| 3-906 | -906 | 11.89 | 0.13 | 1.98 | 0.08 | 0.468 | 0.005 | 0.078 | 0.003 |
| 3-907 | -907 | 13.46 | 0.18 | 2.08 | 0.08 | 0.530 | 0.007 | 0.082 | 0.003 |
| 3-908 | -908 | 16.36 | 0.23 | 2.21 | 0.08 | 0.644 | 0.009 | 0.087 | 0.003 |
| 3-909 | -909 | 17.93 | 0.23 | 2.46 | 0.08 | 0.706 | 0.009 | 0.097 | 0.003 |
| 3-910 | -910 | 19.18 | 0.23 | 2.46 | 0.08 | 0.755 | 0.009 | 0.097 | 0.003 |
| 3-911 | -911 | 21.92 | 0.23 | 2.95 | 0.10 | 0.863 | 0.009 | 0.116 | 0.004 |
| 3-912 | -912 | 23.47 | 0.23 | 2.95 | 0.10 | 0.924 | 0.009 | 0.116 | 0.004 |
| 3-913 | -913 | 25.04 | 0.25 | 2.95 | 0.10 | 0.986 | 0.010 | 0.116 | 0.004 |
| 3-914 | -914 | 26.59 | 0.25 | 2.95 | 0.10 | 1.047 | 0.010 | 0.116 | 0.004 |
| 3-916 | -916 | 29.74 | 0.25 | 2.95 | 0.10 | 1.171 | 0.010 | 0.116 | 0.004 |
| 3-918 | -918 | 34.42 | 0.30 | 2.95 | 0.10 | 1.355 | 0.012 | 0.116 | 0.004 |
| 3-920 | -920 | 37.47 | 0.36 | 3.00 | 0.10 | 1.475 | 0.014 | 0.118 | 0.004 |
| 3-924 | -924 | 43.69 | 0.36 | 3.00 | 0.10 | 1.720 | 0.014 | 0.118 | 0.004 |



AS-568



| Parker Size No. | AS 568A SIZE | METRIC O-RING measurements in millimeters | | | | STANDARD O-RING measurements in inches | | | |
|--------------------|-----------------|--|------|------|------|---|-------|-------|-------|
| | | ID | ± | CS | ± | ID | ± | CS | ± |
| 3-928 | -928 | 53.09 | 0.46 | 3.00 | 0.10 | 2.090 | 0.018 | 0.118 | 0.004 |
| 3-932 | -932 | 59.36 | 0.46 | 3.00 | 0.10 | 2.337 | 0.018 | 0.118 | 0.004 |